



CATEGORY:

CLEARED

ADDRESS
CONTACT IF FOUND:

FORM PTO-1390 (Modified)
(REV 11-98)

U.S. DEPARTMENT OF COMMERCE PATENT AND TRADEMARK OFFICE

ATTORNEY'S DOCKET NUMBER

TRANSMITTAL LETTER TO THE UNITED STATES

KIX0128-PCT

DESIGNATED/ELECTED OFFICE (DO/EO/US)

U.S. APPLICATION NO. (IF KNOWN, SEE 37 CFR

CONCERNING A FILING UNDER 35 U.S.C. 371

- 09/744161

INTERNATIONAL APPLICATION NO.
PCT/JP99/03912INTERNATIONAL FILING DATE
21 JULY 1999PRIORITY DATE CLAIMED
24 JULY 1998

TITLE OF INVENTION

IMAGE PROCESSING APPARATUS

APPLICANT(S) FOR DO/EO/US

HISAYOSHI FUJIMOTO, HIROAKI ONISHI, TOSHIHIKO TAKAKURA AND NORIHIRO IMAMURA

Applicant herewith submits to the United States Designated/Elected Office (DO/EO/US) the following items and other information:

1. ☒ This is a **FIRST** submission of items concerning a filing under 35 U.S.C. 371.
2. ☐ This is a **SECOND** or **SUBSEQUENT** submission of items concerning a filing under 35 U.S.C. 371.
3. ☒ This is an express request to begin national examination procedures (35 U.S.C. 371(f)) at any time rather than delay examination until the expiration of the applicable time limit set in 35 U.S.C. 371(b) and PCT Articles 22 and 39(1).
4. ☒ A proper Demand for International Preliminary Examination was made by the 19th month from the earliest claimed priority date.
5. ☒ A copy of the International Application as filed (35 U.S.C. 371 (c) (2))
 - a. ☒ is transmitted herewith (required only if not transmitted by the International Bureau).
 - b. ☐ has been transmitted by the International Bureau.
 - c. ☐ is not required, as the application was filed in the United States Receiving Office (RO/US).
6. ☒ A translation of the International Application into English (35 U.S.C. 371(c)(2)).
7. ☒ A copy of the International Search Report (PCT/ISA/210).
8. ☐ Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371 (c)(3))
 - a. ☐ are transmitted herewith (required only if not transmitted by the International Bureau).
 - b. ☐ have been transmitted by the International Bureau.
 - c. ☐ have not been made; however, the time limit for making such amendments has NOT expired.
 - d. ☒ have not been made and will not be made.
9. ☐ A translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371(c)(3)).
10. ☒ An oath or declaration of the inventor(s) (35 U.S.C. 371 (c)(4)).
11. ☒ A copy of the International Preliminary Examination Report (PCT/IPEA/409).
12. ☐ A translation of the annexes to the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371 (c)(5)).

Items 13 to 20 below concern document(s) or information included:

13. ☒ An Information Disclosure Statement under 37 CFR 1.97 and 1.98.
14. ☒ An assignment document for recording. A separate cover sheet in compliance with 37 CFR 3.28 and 3.31 is included.
15. ☐ A **FIRST** preliminary amendment.
16. ☐ A **SECOND** or **SUBSEQUENT** preliminary amendment.
17. ☐ A substitute specification.
18. ☐ A change of power of attorney and/or address letter.
19. ☐ Certificate of Mailing by Express Mail
20. ☒ Other items or information:

ACKNOWLEDGEMENT POSTCARD

U.S. APPLICATION NO. (IF KNOWN, SEE 37 CFR 1.53) **-09/744161** INTERNATIONAL APPLICATION NO. **PCT/JP99/03912** ATTORNEY'S DOCKET NUMBER **KIX0128-PCT**

21. The following fees are submitted:

BASIC NATIONAL FEE (37 CFR 1.492 (a) (1) - (5)) :

- ☐ Neither international preliminary examination fee (37 CFR 1.482) nor international search fee (37 CFR 1.445(a)(2)) paid to USPTO and International Search Report not prepared by the EPO or JPO **\$1,000.00**
- ☐ International preliminary examination fee (37 CFR 1.482) not paid to USPTO but International Search Report prepared by the EPO or JPO **\$860.00**
- ☐ International preliminary examination fee (37 CFR 1.482) not paid to USPTO but international search fee (37 CFR 1.445(a)(2)) paid to USPTO **\$710.00**
- ☐ International preliminary examination fee paid to USPTO (37 CFR 1.482) but all claims did not satisfy provisions of PCT Article 33(1)-(4) **\$690.00**
- ☐ International preliminary examination fee paid to USPTO (37 CFR 1.482) and all claims satisfied provisions of PCT Article 33(1)-(4) **\$100.00**

ENTER APPROPRIATE BASIC FEE AMOUNT =

CALCULATIONS PTO USE ONLY

\$860.00

Surcharge of **\$130.00** for furnishing the oath or declaration later than ☐ 20 ☐ 30 months from the earliest claimed priority date (37 CFR 1.492 (e)).

\$0.00

CLAIMS	NUMBER FILED	NUMBER EXTRA	RATE
Total claims	16 - 20 =	0	x \$18.00
Independent claims	2 - 3 =	0	x \$80.00
Multiple Dependent Claims (check if applicable).			<input type="checkbox"/>

\$0.00

\$0.00

\$0.00

TOTAL OF ABOVE CALCULATIONS =

\$860.00

Reduction of 1/2 for filing by small entity, if applicable. Verified Small Entity Statement must also be filed (Note 37 CFR 1.9, 1.27, 1.28) (check if applicable). ☐

\$0.00

SUBTOTAL =

\$860.00

Processing fee of **\$130.00** for furnishing the English translation later than ☐ 20 ☐ 30 months from the earliest claimed priority date (37 CFR 1.492 (f)).

+

\$0.00

TOTAL NATIONAL FEE =

\$860.00

Fee for recording the enclosed assignment (37 CFR 1.21(h)). The assignment must be accompanied by an appropriate cover sheet (37 CFR 3.28, 3.31) (check if applicable). ☒

\$40.00

TOTAL FEES ENCLOSED =

\$900.00

Amount to be:
refunded

\$

charged

\$

☒ A check in the amount of **\$900.00** to cover the above fees is enclosed.

☐ Please charge my Deposit Account No. _____ in the amount of _____ to cover the above fees.
A duplicate copy of this sheet is enclosed.

☒ The Commissioner is hereby authorized to charge any fees which may be required, or credit any overpayment to Deposit Account No. **50-1390** A duplicate copy of this sheet is enclosed.

NOTE: Where an appropriate time limit under 37 CFR 1.494 or 1.495 has not been met, a petition to revive (37 CFR 1.137(a) or (b)) must be filed and granted to restore the application to pending status.

SEND ALL CORRESPONDENCE TO:

Michael D. Bednarek
SHAWPITTMAN
2300 N Street, N.W.
Washington, D.C. 20037-1128

SIGNATURE

MICHAEL D. BEDNAREK

NAME

32,329

REGISTRATION NUMBER

JANUARY 22, 2001

DATE

20/PRT3

09/744161

JG02 Rec'd PCT/PTO 22 JAN 2001

SPECIFICATION

IMAGE PROCESSING APPARATUS

5 TECHNICAL FIELD

The present invention relates to an image processing apparatus capable of both reading and printing an image.

BACKGROUND ART

10 A facsimile machine is an example of an image processing apparatus. The facsimile machine has to have both image reading capability and image printing capability, and further has to be as small as possible.

With this background, there is already a facsimile machine
15 incorporating such a constitution as shown in Fig. 20 as part of the facsimile machine. The illustrated constitution comprises an integrated image-reading/writing head H and two platen rollers P_1 , P_2 . The integrated image-reading/writing head H includes a case 1e having an upper opening fitted with
20 a transparent cover 19e. Inside the case 1e, a light source 3e for illuminating a reading line S_e provided on the transparent cover 19e, and a lens 5e are provided. The case 1e has a bottom surface mounted with a substrate 4e. The substrate 4e has an upper surface 40 and a back surface 41
25 respectively mounted with a plurality of light receiving elements 2e and a plurality of heating elements 8e, linearly and longitudinally of the substrate 4e.

In the image processing apparatus with the constitution described above, a document D is contacted onto the transparent cover 19e and fed by the platen roller P_1 . During this feeding process, the document D is illuminated by the light source 3e.

5 Then, light reflected by the surface of the document D is focused by the lens 5e, forming an image of the document D on the array of the light receiving elements 2e. Each of the light receiving elements 2e outputs read image data of the document line by line. On the other hand, a recording paper K which is
10 thermosensible is contacted onto each of the heating elements 8e and fed by the platen roller P_2 . During this feeding process, selected ones of the heating elements 8e are heated to print the image in the recording paper K line by line.

According to the above facsimile machine, the overall
15 height of the machine can be smaller than a facsimile machine in which the reading head and the printing head are provided separately. Further, the image on the document D can be copied on the recording paper K if print image data is prepared based on the read data outputted from the light receiving elements
20 2e, and this print image data is outputted to the heating elements 8e.

However, the above facsimile machine has the following problems.

First, the two platen rollers P_1 , P_2 are disposed so as to
25 sandwich the whole of the integrated image-reading/writing head. Thus, the entire assembly of the integrated image-reading/writing head and the two platen rollers P_1 , P_2 has a large

dimension thickness-wise of the integrated image-reading/writing head H. Therefore, the thickness of the facsimile machine as a whole is still large.

Second, when manufacturing the integrated image reading/writing head H, first, the light receiving elements 2e must be mounted on the upper surface 40 of the substrate 4e, and then the substrate 4e must be turned over in order to mount the heating elements 8e on the back surface 41 of the substrate 4e. Further, a wiring pattern relevant to the light receiving elements 2e and another wiring pattern relevant to the heating elements 8e must be formed respectively in the upper surface 40 and the back surface 41 of the substrate 4e. Therefore, productivity in the manufacture of the integrated image reading/writing head H is low.

DISCLOSURE OF THE INVENTION

It is therefore an object of the present invention to provide an image processing apparatus capable of solving or reducing the problems in the prior art and capable of copying the image of the document.

The image processing apparatus provided by a first aspect of the present invention comprises: an integrated image-reading/writing head including a transparent cover, a substrate opposed to and spaced from the transparent cover, a plurality of light receiving elements mounted in a row on the substrate and capable of reading in a main scanning direction an image on a document faced onto the transparent

cover whereby outputting line by line read image data containing a first to an n-th pixel data, and a plurality of printing elements mounted in a row generally in parallel to the light receiving elements on the substrate and capable of
5 outputting printing image data onto a recording paper for printing;

a platen roller for the document, facing the transparent cover;

a platen roller for the recording paper, facing the printing
10 elements; and

data processing means capable of creating the printing image data containing a first to a n-th printing pixel data respectively corresponding to the first to the n-th pixel data in the read image data; and is characterized by

15 that the light receiving elements and the printing elements are mounted on a same surface of the substrate;

that a feeding direction of the document in a region where the document is faced to the transparent cover and a feeding direction of the recording paper in a region where the recording
20 paper is faced to the printing elements are the same; and

that the pixel data outputted for the printing are arranged in the order of first to n-th when the printing image data are outputted by the printing elements onto the recording paper for printing.

25 According to the image processing apparatus having the constitution described above, the following effects are obtained.

First, the two platen rollers for the document and for the recording paper can be faced directly or indirectly to the corresponding light receiving elements and printing elements provided on the same surface of the substrate of the integrated image-reading/writing head. Thus, differing from the prior art, there is no need for disposing the two platen rollers to sandwich the whole of the integrated image-reading/writing head, and it becomes possible to make the two platen rollers not to overlap thickness-wise of the integrated image-reading/writing head, thereby making the apparatus as a whole thinner than before.

Second, when manufacturing the integrated image-reading/writing head, the light receiving elements and the printing elements should be mounted merely on one same surface of the substrate. Therefore, there is no need to turn over the substrate in order to mount these components. Further, the wiring patterns for these light receiving elements and the printing elements can be formed on the same surface of the substrate. Therefore, it becomes possible to increase productivity in the manufacture of the integrated image-reading/writing head, and productivity in the manufacture of the image processing apparatus incorporating the integrated image-reading/writing head than in the prior art.

Third, when creating printing image data based on the read image data obtained by reading the image on the document, and outputting the printing image data onto the recording paper for printing, i.e. when copying the document, the copying

operation can be performed appropriately. More specifically, when copying the document, the output is made in such a way that pixel data contained in the printing image data are lined up in the order of first to n-th in the main scanning direction.

5 The order of the pixel data outputted as described is the same as the order of the first to the n-th pixel data in the original read image data when the document is read in the main scanning direction. On the other hand, the feeding direction of the document in the region where the document is faced to the transparent cover and the feeding direction of the recording paper in the region where the recording paper is faced to the printing elements are the same. Therefore, the image printed on the recording paper is not an inverted image of the document.

10 According to a preferred embodiment of the present invention, the integrated image-reading/writing head is provided with a drive controlling circuit including a shift register serially storing the pixel data contained in the printing image data received from the data processing means in the order of reception and in the direction of the row of printing elements, and selectively driving the printing elements corresponding to contents of the pixel data stored in the shift register. Further, the inputting direction of the printing image data to the shift register is opposite to the main scanning direction.

25 With the above arrangement, when the printing image data containing the pixel data arranged in the order of first to n-th are sent from the data processing means to the shift

register, the pixel data are serially stored in the order of first to n-th in the main scanning direction. This is because the shift register is a storing device in which data storage is made by sequentially shifting the data longitudinally of the shift register so that the datum received first is stored at the farthest location, and according to the above described arrangement, inputting of the data to the shift register is made from the direction opposite to the main scanning direction. For this reason, when the printing elements are driven corresponding to the content of the pixel data stored in the shift register, the pixel data contained in the printing image data are outputted for printing on the recording paper in the order of first to n-th in the main scanning direction. As a result, the image printed on the recording paper is not an inverted image of the document.

The image processing apparatus provided by a second aspect of the present invention comprises:

an integrated image-reading/writing head including a transparent cover, a substrate opposed to and spaced from the transparent cover, a plurality of light receiving elements mounted in a row on the substrate and capable of reading in a main scanning direction an image on a document faced onto the transparent cover whereby outputting line by line read image data containing a first to an n-th pixel data, and a plurality of printing elements mounted in a row generally in parallel to the light receiving elements on the substrate and capable of outputting printing image data onto a recording

paper for printing;

a platen roller for the document, facing the transparent cover;

a platen roller for the recording paper, facing the printing
5 elements; and

data processing means capable of creating the printing image data containing a first to a n-th printing pixel data respectively corresponding to the first to the n-th pixel data in the read image data; and characterized by

10 that the light receiving elements and the printing elements are mounted on a same surface of the substrate;

that a feeding direction of the document in a region where the document is faced to the transparent cover and a feeding direction of the recording paper in a region where the recording
15 paper is faced to the printing elements are opposite to each other; and

that the pixel data outputted for the printing are arranged in the order of n-th to first when the printing image data are outputted by the printing elements onto the recording paper
20 for printing.

According to the image processing apparatus having the above constitution, the same effect as obtained in the image processing apparatus provided by the first aspect of the present invention can be obtained. The image processing
25 apparatus provided by the second aspect of the present invention differs from the image processing apparatus provided by the first aspect of the present invention in relationship

between the feeding direction of the document and the feeding direction of the recording paper, and in the order of the pixel data when the printing image data are outputted onto the recording paper for printing. However, with this constitution,
5 it is also possible to copy a document appropriately. Specifically, when copying a document, the output to the recording paper is made in such a way that pixel data contained in the printing image data are lined up in the order of n-th to first in the main scanning direction. The order of the
10 pixel data outputted as described is the opposite, i.e. from first to n-th, to the order of the pixel data in the original read image data when the document is read in the main scanning direction. However, the feeding direction of the document in the region where the document is faced to the transparent cover
15 and the feeding direction of the recording paper in the region where the recording paper is faced to the printing elements are opposite to each other. Therefore, the image printed on the recording paper is not an inverted image of the document.

According to the preferred embodiment of the present
20 invention, the integrated image-reading/writing head is provided with a drive controlling circuit including a shift register serially storing the pixel data contained in the printing image data received from the data processing means in the order of reception and in the direction of the row of
25 printing elements, and selectively driving the printing elements corresponding to contents of the pixel data stored in the shift register. Further, the inputting direction of

the printing image data to the shift register is the main scanning direction.

According to the above arrangement, when the printing image data containing the pixel data arranged in the order of first to n-th are sent from the data processing means to the shift register, the pixel data are serially stored in the order of n-th to first in the main scanning direction. For this reason, when the printing elements are driven corresponding to the content of the pixel data stored in the shift register, the pixel data contained in the printing image data are outputted for printing on the recording paper in the order of n-th to first in the main scanning direction. As a result, the image printed on the recording paper is not an inverted image of the document.

According to another preferred embodiment of the present invention, the drive controlling circuit is constituted by using a plurality of IC chips each incorporating a circuit as a unit of the drive controlling circuit. Further, the IC chips are mounted on the surface of the substrate mounted with the light receiving elements and the printing elements.

With the above arrangement, the drive controlling circuit can be built easily by using the IC chips. Further, when mounting these IC chips on the substrate, there is no need for turning the substrate over, and the mounting operation can be performed easily.

According to still another embodiment of the present invention, the drive controlling circuit incorporates a

circuit as a unit of the drive controlling circuit, and the IC chips also incorporates the light receiving elements.

With the above arrangement, mounting operation of each of the drive controlling circuit and the light receiving elements is simplified, making possible to further increase productivity in the manufacture of the integrated image-reading/writing head and the image processing apparatus incorporating the integrated image-reading/writing head.

According to still another embodiment of the present invention, the drive controlling circuit is arranged to perform drive control of the printing elements when receiving a strobe signal from the data processing means, and the light receiving elements is arranged to perform reading of the document only while the strobe signal is outputted from the data processing means.

With the above arrangement, it becomes possible that ON-OFF switching of the strobe signal is not made while the light receiving elements are reading the image. Therefore, noise caused by the ON-OFF switching of the strobe signal can be prevented from mixing into the read image data. Thus, quality of the read image can be increased.

According to still another preferred embodiment of the present invention, the integrated image-reading/writing head is provided with a case fitted with the transparent cover, the case is assembled to the substrate to enclose the light receiving elements, allowing part of the substrate to extend out of the case, and the printing elements is mounted on the

extended part of the substrate.

With the above arrangement, the light receiving elements can be appropriately enclosed by the case while appropriately reserving space on a side of the case for facing the platen
5 roller for the recording paper onto the printing elements.

According to still another preferred embodiment of the present invention, the surface of the substrate mounted with the light receiving elements and the printing elements is mounted with a light source for illumination of the document.

10 With the above arrangement, operation of assembling the light source into the integrated image-reading/writing head can be simplified.

According to still another preferred embodiment of the present invention, the printing elements are heating elements.

15 With the above arrangement, it becomes possible to print by means of a thermal-transfer method or a thermosensible method.

Other characteristics and advantages of the present invention will become clearer from the description of the preferred embodiments hereinafter.

20

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a simplified sectional view of a first embodiment of the image processing apparatus according to the present invention.

25 Fig. 2 is a perspective view of an integrated image-reading/writing head used in the image processing apparatus in Fig. 1.

Fig. 3 is a sectional view taken in lines III-III in Fig. 2.

Fig. 4 is an exploded perspective view of the integrated image-reading/writing head in Fig. 2.

5 Fig. 5 is a plan view of a principal portion of the integrated image-reading/writing head in Fig. 2.

Fig. 6 is a circuit block diagram of a circuit constituted by a plurality of sensor IC chips of the integrated image-reading/writing head in Fig. 2.

10 Fig. 7 is a circuit block diagram of a plurality of drive IC chips of the integrated image-reading/writing head in Fig. 2.

Fig. 8 is a simplified perspective view showing a state of operation of the image processing apparatus in Fig. 1.

15 Fig. 9 is a plan view showing a principal portion of a second embodiment of the image processing apparatus according to the present invention.

Fig. 10 is a plan view of an IC chip of the image processing apparatus in Fig. 9.

20 Fig. 11 is a diagram showing a principal portion of a third embodiment of the image processing apparatus according to the present invention.

Fig. 12 is a perspective view showing a state of operation of the image processing apparatus in Fig. 11.

25 Fig. 13 is a diagram showing a principal portion of a fourth embodiment of the image processing apparatus according to the present invention.

Fig. 14 is a perspective view of a principal portion showing a state of operation of the image processing apparatus in Fig. 13.

Fig. 15 is a simplified plan view of an integrated image-reading/writing head used in the image processing apparatus in Fig. 13.

Fig. 16 is a circuit block diagram of an IC chip of the integrated image-reading/writing head used in the image processing apparatus in Fig. 13.

Fig. 17 is a diagram showing a principal portion of a fifth embodiment of the image processing apparatus according to the present invention.

Fig. 18 is a diagram of showing a principal portion of a sixth embodiment of the image processing apparatus according to the present invention.

Fig. 19 is a perspective view of a principal portion showing a state of operation of the image processing apparatus in Fig. 18.

Fig. 20 is a sectional view showing a principal portion of a prior art image processing apparatus.

BEST MODE FOR CARRYING OUT THE INVENTION

Hereinafter, embodiments of the present invention will be described with reference to the attached drawings.

Fig. 1 ~ Fig. 8 show a first embodiment of the present invention. As clearly shown in Fig. 1, an image processing apparatus B according to the present embodiment comprises an

integrated image-reading/writing head A, a platen roller P_1 for feeding a document D, a platen roller P_2 for feeding a recording paper K, and a data processing circuit 7. All of these components are incorporated within a box 9. The recording
5 paper K is a long ribbon of thermosensible paper unwound from a roll R. Alternatively however, according to the present invention, the recording paper K may be a cut sheet of paper.

As clearly shown in Fig. 3 and Fig. 4, the integrated image-reading/writing head A includes a case 1, a transparent
10 cover 19, a lens array 5, and a substrate 4.

The substrate 4 is made of a ceramic for example, and is formed into an oblong rectangular plate. The substrate 4 has an upper surface 4a mounted with a plurality of light sources 3, a plurality of sensor IC chips 2, a plurality of drive IC
15 chips 80, and a plurality of heating elements 8.

The light sources 3 are provided by an LED chip for example, and mounted linearly and longitudinally of the substrate 4 at an appropriate interval. Each of the sensor chips 2 is provided by a semiconductor chip including an integrally formed
20 plurality of light receiving elements 20 and mounted linearly and longitudinally of the substrate 4. Each of the sensor IC chips 2 is so arranged that when the light receiving elements 20 receive light, read image signal (read image data) having a level corresponding to an amount of the light received is
25 outputted, and transmitted to the data processing circuit 7. Specific details about the circuitry in each of the sensor IC chips 2 will be described later.

The heating elements 8 are an example of the printing elements according to the present invention. The heating elements 8 can be formed by electrically dividing a heating resistor extending longitudinally of the substrate 4.

5 Specifically, the heating resistor can be formed for example by printing and baking a thick film of resistor paste including an electrically conducting component such as ruthenium oxide. Then, a wiring pattern which electrically divides the heating resistor at a predetermined interval longitudinally of the
10 heating resistor is formed. Each of the drive IC chips 80 incorporates circuitry for heating a plurality of the heating elements 8, and mounted in a row longitudinally of the substrate 4 at an appropriate interval. Specific details about the circuitry in each of the drive IC chips 80 will be described
15 later.

The upper surface 4a of the substrate 4 is formed with wiring patterns (not illustrated) respectively related to the light sources 3, the sensor IC chips 2, the drive IC chips 80 and the heating elements 8. Further, one or more connectors
20 electrically connected with the wiring patterns are provided at an appropriate location(s) of the substrate 4. The connector mutually connects the above described electronic components mounted on the substrate 4 and the data processing circuit 7, making possible to supply power to each of the above
25 described components as well as to input and output various signals.

The back surface 4b of the substrate 4 may be provided with a heat radiating plate (not illustrated) made of a metal having a high thermal conductivity. This arrangement allows to release heat generated by the heating elements 8 and the light sources 3 from the substrate 4 via the radiating plate, making possible to stabilize the temperature of the heating elements 8.

The case 1 is made of a whity synthetic resin material such as polycarbonate containing titanium oxide, and has a length generally the same as of the substrate 4. As clearly shown in Fig. 3, the case 1 is assembled to the upper surface 4a of the substrate 4, surrounding each of the light sources 3, the sensor IC chips 2 and the drive IC chips 80. The case 1 is formed with a thickness-wise through hole 10, and a bottom surface formed with a recess 11. The light sources 3 are disposed on the bottom surface within the through hole 10. the sensor IC chips 2 and the drive IC chips 80 are disposed in the recess 11. The substrate 4 has an edge portion 4c extended out onto one side of the case 1. The heating elements 8 are mounted on this extended portion. The case 1 has a side surface 1a rising from the extended portion of the substrate 4. The side surface 1a is slanted to be farther away from the heating elements 8 at a higher elevation of the case 1.

The transparent cover 19 is to guide the document D, and is formed as a plate of transparent glass or synthetic resin. The transparent resin 19 is opposed to and spaced from the substrate 4, and is fitted into a recess 13 provided in the

upper surface of the case 1. The transparent cover 19 is slanted to the substrate 4, so that the distance to the substrate 4 increases toward the edge portion 4c of the substrate 4. This is for a purpose of reserving a space between the two platen rollers P_1 , P_2 without increasing a space between the platen roller P_1 and the substrate 4. The present invention is not limited by this arrangement however. For example, the transparent cover 19 and the substrate 4 may be in parallel to each other.

The lens array 5 includes a plurality of rod lenses 51 held in a row by an oblong, narrow, block-like lens holder 50. The lens array 5 is fitted into a groove 12 of the case 1, thereby faced toward the back surface of the transparent cover 19. The upper surface of the transparent cover 19 includes an image reading line S in a region facing the lens array 5. The reading line S extends longitudinally of the transparent cover 19. Each of the rod lenses 51 focuses light from the image reading line S onto the array of the light receiving elements 20, forming a line of image of the document D on the light receiving elements 20 without magnification nor inversion. According to the present invention however, the rod lenses may be substituted by other lenses of a different type.

Inside the case 1, a first light path 14a and a second light path 14b are provided. The first light path 14a is provided by the through hole 10, for introducing the light emitted by the light sources 3 to the image reading line S. The second light path 14b includes the groove 12, and is a path for

introducing the light reflected from the image reading line S onto the light receiving elements 20 via the lens array 5. As has been mentioned, the case 1 is formed of a white synthetic resin, and therefore the case 1 is entirely white, having a high reflectance. Thus, the light from the light sources 3 can be guided to the image reading line S, while being reflected at a high rate by the white walls along the first light path 14a, making possible to increase radiation efficiency of the light to the image reading line S.

The case 1 has a bottom portion fitted by an assisting member 6 surrounding the sensor IC chips 2. The assisting member 6 is made for example of an ABS resin containing a black pigment, which colors the surfaces in black, to have a high rate of light absorption. With such an arrangement as above, possibility that the light reflects irregularly around the light receiving elements 20 can be eliminated and therefore, quality of the read image can be increased. The assisting member 6 has an upper portion formed with projections 60, which are fitted into corresponding recesses 15 formed in the case 1, thereby assembling the assisting member to the case 1.

Fig. 6 shows a specific constitution of the sensor IC chips 20. It should be noted however, that this figure conceptually shows a case in which a plurality of sensor IC chips 2 are connected in series into one circuit. This particular circuit includes a plurality of phototransistors $PT_1 \sim PT_n$ which provides the plurality (n) of the light receiving elements 2, the plurality of $FET_1 \sim FET_n$ respectively connected to the emitter

side of the phototransistors $PT_1 \sim PT_n$, an amplifier OP for amplifying the electric current from the $FET_1 \sim FET_n$, an n-bit shift register 29, a pad VDD, a pad GND, a pad AO, a pad SI, a pad CLK, and a pad SO. The pad VDD is supplied with power voltage of 5 V for example. The pad GND is grounded. The pad CLK is supplied with a clock signal of 8 MHz for example. If the document D to be read is of the size A4 and the reading is made at a reading density of 8 dots/mm for example, a total of 1728 light receiving elements 20 must be disposed. Therefore, if a total of 96 light receiving elements 20 is formed in each of the sensor IC chips 2, a total of 18 sensor IC chips 2 are mounted linearly on the substrate 4, and these 18 sensor IC chips 2 are electrically connected in series.

According to the above circuit, when a serial-in signal is inputted to the pad SI first, the shift register 29 sequentially turns on the $FET_1 \sim FET_n$ in a predetermined direction (main scanning direction) based on the clock signal. Then, electric charges corresponding to the amount of the light received and stored in the phototransistors $PT_1 \sim PT_n$ are discharged sequentially in a predetermined order, amplified by the amplifier OP, and then serially outputted to the pad AO. This output signal is an analog signal and is a signal including the read image data according to the present invention. When the electric charges have been discharged from the last phototransistor PT_n in the operation of the shift register 29, a serial-out signal is outputted to the pad SO. The circuit can repeatedly perform the above described cycle

of operations, in which the read image data is outputted line by line. One phototransistor corresponds to one reading pixel. Therefore, the above one line of read image data contains the same number of pixel data as the number of the light receiving elements 20, i.e. the first pixel datum to the n-th pixel datum. The read image data serially outputted to the pad AO is transmitted to the data processing circuit 7.

Referring to Fig. 1, the data processing circuit 7 corresponds to the data processing means according to the present invention, and includes for example, a CPU and accompanying memories, or a circuit to convert image data into binary values. The data processing circuit 7 is not only capable of processing the image data but also capable of controlling the reading operation of the image on the document D by using the light receiving elements 20, and outputting of the image data for printing on the recording paper K. The data processing circuit 7 also performs transmission of various signals mentioned above. Further, the data processing circuit 7 performs transmission of various signals to the drive IC chips 80 as will be described later. As part of the data processing function, the data processing circuit 7 creates printing image data, i.e. data for printing an image, based on the read image data outputted from the pad SO of the sensor IC chips 2, and send the printing image data to the drive IC chips 80.

As clearly shown in Fig. 7, each of the drive IC chips 80 includes a shift register 89, a latch circuit LT, a plurality (n) of AND circuits $AND_1 \sim AND_n$, the plurality of bipolar

transistors $TR_1 \sim TR_n$, the plurality of pads $PO_1 \sim PO_n$, and various other pads. It should be noted here that the number of bits "n" of the circuitry built in one drive IC chip 80 has a different value from the number of bits "n" of the circuit as a whole shown in Fig. 6. The pads $PO_1 \sim PO_n$ are electrically connected with the heating elements 8. For example, if recording is made on the recording paper K of the width of size A4 at a printing density of 8 dots/mm, a total of 1728 heating elements 8 must be disposed. Therefore, if each of the drive IC chips 80 incorporates a total of 144 pads $PO_1 \sim PO_n$, and the same number of bipolar transistors $TR_1 \sim TR_n$, a total of twelve drive IC chips 80 are mounted in a row generally in parallel to the heating elements 8 (See Fig. 5.). The pads $PO_1 \sim PO_n$ are respectively connected with the heating elements 8 via a wiring portion 47. The drive IC chips 80 are electrically connected in series via a pattern-formed wiring portion 48.

Electrical connection between a pair of mutually adjacent IC chips 80 is as shown in Fig. 7. Specifically, the pad STRO, the pad LATO, the pad CLKO, and the pad DO of one IC chip 80 are connected with the pad STRI, the pad LATI, the pad CLKI, and the pad DI of the other IC chip 80 respectively. Each of the strobe signal sent to the pad STRI, the latch signal sent to the pad LATI, the clock signal sent to the pad CLKI, and the printing image data sent to the pad DI of said one drive IC chip 80 can be transferable to said other drive IC chip 80. The pad GND is grounded individually for each drive IC chip 80.

The shift registers 89 incorporated respectively in the drive IC chips 80 are connected in series. The shift registers 89 can store printing image data for one line (for example, image data containing 1728 bits of binary pixel data) sent to the pad DI from the data processing circuit 7, serially in the order of transmission from the data processing circuit 7. More specifically, as clearly shown in Fig. 5, the printing image data for one line is inputted in the direction indicated by Arrow Na, i.e. from a right end 89b toward a left end 89a of the array of shift registers 89, and stored. This direction of input of the printing image data is the opposite of the main scanning direction Nb of the light receiving elements 20. The main scanning direction Nb according to the present embodiment is the direction, as in Fig. 5, from a left end 20a toward a right end 20b of the array of the light receiving elements 20.

As shown in Fig. 7, the image data stored in each of the shift registers 89 is then latched in the latch circuit LT. Under this state, when the strobe signal is sent from the data processing circuit 7 to the pad STRI, one of the input ends in each of the AND circuits $AND_1 \sim AND_n$ assumes the high level. On the other hand, the other input end in each of the AND circuits $AND_1 \sim AND_n$ assumes either one state of the high level and the low level depending on the content of the printing image data latched in the latch circuit LT. If this other input end assumes the high level, the output end of this AND circuit also assumes the high level, turning on corresponding one of the bipolar transistors TR and therefore applying electric current

via the corresponding pad P0 to the corresponding heating element 8. According to the present embodiment, since the circuitry incorporated in the drive IC chips 80 are connected in series, the resulting drive control circuit is capable of driving all of the heating elements 8 selectively.

The data processing circuit 7 is arranged to send the serial-in signal to the sensor IC chips 2 simultaneously with or right after the commencement of strobe signal transmission to the drive IC signals 80. Because of this arrangement, reading operation of the line of document image is performed only during the time in which the strobe signal is being sent from the data processing circuit 7. Arrangement of the heating elements 8 may not necessarily be that all of the heating elements 8 are driven at one time. For example, the arrangement may be that the strobe signal is inputted to a plurality of groups of the heating elements 80 at a certain delay. With such an arrangement as this, the heating elements 8 can be divided into a plurality of groups and driven at a different timing. Even in such a case as this, the light receiving elements 20 are so arranged that the reading of the document image is made only during the period in which one of these strobe signals are being outputted.

As clearly shown in Fig. 1, the platen roller P_1 faces the transparent cover 19, and is driven to rotate in the direction indicated by Arrow Nc so as to feed the document D under tight contact with the transparent cover 19 continuously or intermittently in the secondary scanning direction. On the

other hand, the platen roller P_2 faces the heating elements 8, and is driven to rotate so as to feed the recording paper K between the platen roller itself and the heating elements 8 continuously or intermittently. The rotating direction of the platen roller P_2 is the same as of the platen roller P_1 , and indicated by Arrow Nd. Therefore, the feeding direction of the document D on the transparent cover 19 and the feeding direction of the recording paper k on the heating elements 8 are the same. According to the present embodiment, the feeding angle of the document D on the transparent cover 19 and the feeding angle of the recording paper K on the heating elements 8 are different, and in a strict sense, the feeding directions of the document D and the recording paper k are not identical. However, such a difference in the feeding angle of the document D and the recording paper K as the above is not included in the concept of the sameness in the feeding direction of the document D and the recording paper K. According to the present invention, if the two platen rollers P_1 , P_2 rotate in a same direction, then the document D and the recording paper K respectively fed by these rollers are also fed in the same direction.

Next, function of the image processing apparatus B will be described.

First, since the integrated image-reading/writing head A is capable of both image reading operation and printing operation, image reading of document D and image printing on recording paper K can be performed individually or

simultaneously. Both of the platen rollers P_1 , P_2 are disposed above the substrate 4 of the integrated image-reading/writing head A, and the platen roller P_2 overlaps the integrated image-reading/writing head A height-wise of the image processing apparatus B. Therefore, the image processing apparatus B can be made thinner than before. The side surface 1a of the case 1 is slanted to be farther away from the platen roller P_2 . Therefore, space-efficient disposition of the platen roller P_2 can be made while making the extension of the edge portion 4a of the substrate 4 relatively small. Therefore, size reduction of the image processing apparatus B can be further prompted.

When the platen rollers P_1 , P_2 are assembled into the box 9, the platen rollers are assembled from above the integrated image-reading/writing head A. Further, the platen rollers P_1 , P_2 press the transparent cover 2 and the heating elements 8 respectively in the same direction. This makes easy the assembling operation of the platen rollers P_1 , P_2 .

As shown in Fig. 3, the constitution of the integrated image-reading/writing head A is that each of the light sources 3, the sensor IC chips 2 including the light receiving elements 2, the drive IC chips 80 and the heating elements 8 are mounted on the upper surface 4a of the substrate 4. Further, the wiring patterns related to these components are formed also on the upper surface 4a. Therefore, when forming the wiring patterns and mounting each of these components, there is no need for turning the substrate 4 over. Therefore, productivity can be

improved.

According to the integrated image-reading/writing head B, the following operations are performed when copying an image on the document.

5 Specifically, first, reading operation of the image on the document D is performed. As shown in Fig. 5, when the image on the document D is read in the main scanning direction Nb, the read image data for a line outputted from the light receiving elements 20 provides an array of pixel data sequentially read
10 from a left end Da to the right end Db of the document D. More specifically, if individual pixel data of a line read by the light receiving elements 20, from the left-end element 20a to the right-end element 20b, are represented respectively by G1, G2, G3 ~ G_n, then, as shown in the figure, the read image data
15 of the line includes these pixel data in the order of reading, i.e. in the order of G1, G2, G3 ~ G_n, and is outputted from the light receiving elements 20 to the data processing circuit 7.

 The data processing circuit 7, upon receiving the read image data, creates printing image data by converting the image data
20 into binary values representing black or white. The printing image data is then serially sent line by line to the shift registers 89. The printing image data is an image data containing the same number of pixel data G1', G2', G3' ~ G'_n as the binary conversion of the pixel data G1, G2, G3 ~ G_n without
25 changing the order. This printing image data is inputted to the shift registers 89 in the direction indicated by Arrow Na in Fig. 5, i.e. from the right-end shift register 89b.

Therefore, within the shift registers 89, the printing data is stored serially from the left-end shift register 89a to the right-end shift register 89b, i.e. in the order of G'1, G'2, G'3 ~ G'n in the main scanning direction Nb. With this arrangement, the heating elements 8 are selectively driven for print output of the printing image data. The printing is made on a downward facing surface of the recording paper K which is being fed in the same direction as in the document D, and the pixel data G'1, G'2, G'3 ~ G'n are printed from a left end Ka to a right end Kb of the recording paper K. As a result, as shown in Fig. 8, the image printed on the recording paper K accurately corresponds to the image on the document D, without becoming a mirror symmetry image of the original image on the document D.

The document copying operation is performed by repeating the above described cycle of processes line by line. However, as has been described earlier, according to the image processing apparatus B, the reading operation by the light receiving elements 20 is performed only during the period in which the strobe signal is being sent to the drive IC chips 80. Therefore, potential inclusion of noise caused by the rising and/or falling of the strobe signal into the image data can be eliminated, and therefore quality of read image data can be improved.

Fig. 9 and Fig. 10 show a second embodiment of the present invention. It should be noted here however, that in Fig. 9 and thereafter, elements same as or similar to those in the

first embodiment are indicated by the same alpha-numeral codes.

According to the arrangement shown in Fig. 9, a plurality of IC chips 2A are mounted in a row on the upper surface of the substrate 4. In each of the IC chips 2A, the circuit built in the sensor IC chip 2 and the circuit built in the drive IC chip 80 described in the first embodiment are incorporated within a single chip. As clearly shown in Fig. 10, each of the IC chips 2A has an upper surface provided with a plurality of pads P0 to connected with the light receiving elements 20 and the heating elements, and other pads for signal input and output. The IC chips 2A are electrically connected in series with each other, thereby constituting a circuit including the necessary number of light receiving elements 20 for reading a line of document and a circuit capable of controlling all of the heating elements 8 for selective driving.

According to the present invention, the image processing apparatus B described in the first embodiment can be constituted by using the IC chips 2A. According to such a constitution as this, the total number of the IC chips mounted on the substrate 4 can be decreased, and the number of steps for mounting the IC chips on the substrate 4 can be decreased. Inputting direction of the printing image data to the IC chips 2A is made the same as in the case shown in Fig. 5, so that the image printed on the recording paper is not inversed in a copy of the document image.

Fig. 11 and Fig. 12 show a third embodiment of the present invention.

As clearly shown in Fig. 11, in an image processing apparatus Ba according to the present embodiment, rotating direction of the platen rollers P_1 , P_2 is the opposite to the rotating direction of the platen rollers P_1 , P_2 in the first embodiment. However, even if the rotating direction of the two platen rollers P_1 , P_2 is reversed, the feeding direction of the document D on the transparent cover 12 and the feeding direction of the recording paper K on the heating elements 8 are the same. Therefore, according to the image processing apparatus Ba, as shown in Fig. 12, the image on the document D can be appropriately printed on the recording paper K without mirror inversion if the inputting of the printing image data into the shift registers incorporated in the drive IC chips 80 is in the direction indicated by Arrow Na, which is the opposite direction to the main scanning direction Nb. The main scanning direction Nb is the direction in which the light receiving elements 20 read the image on the document D. Specifically, according to the image processing apparatus Ba, the image on the document D is read from the right end Db to the left end Da of the document whereas the pixel carrying the printing image data corresponding to the right end Db is printed at a right end Kb of the recording paper K. Likewise, the pixel carrying the printing image data corresponding to the left end Da of the document D is printed at a left end Ka of the recording paper K. Therefore, the constitution of the image processing apparatus Ba can be exactly the same as the image processing apparatus B according to the first embodiment, differing from

the image processing apparatus B according to the first embodiment only in that the platen rollers P_1 , P_2 rotate in the opposite direction.

Fig. 13 ~ Fig. 16 show a fourth embodiment of the present invention.

As clearly shown in Fig. 13, in an image processing apparatus Bb according to the present embodiment, the platen roller P_1 rotates in the direction indicated by Arrow Nc whereas the platen roller P_2 rotates in the opposite direction indicated by Arrow Ne. As a result, the feeding direction of the document D on the transparent cover 12 and the feeding direction of the recording paper K on the heating elements 8 are opposite to each other. As shown in Fig. 16, in each of the drive IC chips 80a used in an integrated image-reading/writing head Aa of this image processing apparatus Bb, disposition pattern of the various pads for inputting and outputting signals and data is a mirror-inversion of the disposition pattern in the drive IC chips 80 shown in Fig. 7. Further, the inputting of the data to shift registers 89A is made from the left end of the array. If the drive IC chips 80a with the above arrangement are used, the wiring pattern formed on the upper surface 4a of the substrate 4 must be altered accordingly. However, the necessary alteration is only that the wiring pattern on the substrate 4 in the image processing apparatus B should be mirror inverted. Therefore, the alteration of the wiring pattern can be performed simply by turning over the pattern forming mask used for the substrate 4.

According to the image processing apparatus Bb, as shown in Fig. 15, first, the light receiving elements 2 performs reading of the document image in the main scanning direction indicated by Arrow Nb. Then, read image data containing pixel data $G_1, G_2, G_3 \sim G_n$ is serially outputted. Then, the data processing circuit 7 creates printing image data containing pixel data $G'_1, G'_2, G'_3 \sim G'_n$ as binary conversion of the pixel data $G_1, G_2, G_3 \sim G_n$ without changing the order. Then this printing image data is inputted from the left end of the array of shift registers 89A as indicated by Arrow Nh.

According to the image processing apparatus Bb, the pixel data of the printing image data is stored in the order of $G'_1, G'_2, G'_3 \sim G'_n$ from the right end to the left end of the array of shift registers 89A, and then outputted on the recording paper K in the same order. Direction of the array in the pixel data $G'_1, G'_2, G'_3 \sim G'_n$ of the printing image data printed as the above, is the opposite to the direction of the array in the pixel data $G_1, G_2, G_3 \sim G_n$ of the original read image data. However, since the recording paper K and the document D are fed in opposite directions to each other, result is the appropriate printing on the recording paper, without mirror-inverting the original image on the document D.

Fig. 17 shows a fifth embodiment of the present invention.

According to the constitution shown in the figure, a plurality of IC chips 2B are mounted in a row on a surface of the substrate 4. Each of the IC chips 2B incorporates, as in the IC chips 2A in the second embodiment, the image reading

circuit provided with light receiving elements 20 and the drive control circuit for the heating elements in a single chip. The constitution of the drive control circuit is identical with the constitution shown in Fig. 16.

5 According to the present invention, the image processing apparatus Bb in the fourth embodiment can be constituted by using the IC chips 2B. According to this constitution, as in the second embodiment, the total number of the IC chips mounted on the substrate 4 can be decreased, and therefore productivity
10 in the manufacture of the integrated image-reading/writing head can be increased. Inputting direction of the printing image data to the IC chips 2B is made the same as in the case shown in Fig. 15, so that the image printed on the recording paper is not an inversed image when a document image is copied.

15 Fig. 18 and Fig. 19 show a sixth embodiment of the present invention.

As clearly shown in Fig. 18, in an image processing apparatus Bc according to the present embodiment, rotating directions Nf, Ng of the two platen rollers P_1 , P_2 respectively
20 are the opposite to the rotating directions of the platen rollers P_1 , P_2 in the third embodiment. Therefore, again in this image processing apparatus Bc, as in the image processing apparatus Bb, the feeding direction of the document D on the transparent cover 19 and the feeding direction of the recording
25 paper K on the heating elements 8 are opposite to each other. Therefore, according to the image processing apparatus Bc, as shown in Fig. 19, the image on the document D can be

appropriately printed on the recording paper K without mirror inversion if the inputting of the printing image data into the shift register incorporated in the drive IC chips 80a is in the direction indicated by Arrow Nh, which is the same direction to the main scanning direction Nb. Therefore, the constitution of the image processing apparatus Bc can be exactly the same as of the image processing apparatus Bb, differing from the image processing apparatus Bb only in that the platen rollers P₁, P₂ rotate in the opposite directions.

In the above described embodiments, as means for performing appropriate image printing (without mirror inversion), the inputting direction of the printing image data into the shift registers is changed depending on the feeding direction of the document and the recording paper. However, the present invention is not limited to this. According to the present invention, for example, a desired array of the printing image data stored in the shift registers may be achieved by swapping or not swapping the first datum and last datum thereby changing the order of the pixel data when the printing image data created by the data processing circuit is sent line by line.

Specific arrangements in the image processing apparatus according to the present invention are not limited to those described in the embodiment and can be varied in many ways.

CLAIMS

1. An image processing apparatus comprising:

an integrated image-reading/writing head including a
transparent cover, a substrate opposed to and spaced from the
transparent cover, a plurality of light receiving elements
mounted in a row on the substrate and capable of reading in
a main scanning direction an image on a document faced onto
the transparent cover whereby outputting line by line read
image data containing a first to an n-th pixel data, and a
plurality of printing elements mounted in a row generally in
parallel to the light receiving elements on the substrate and
capable of outputting printing image data onto a recording
paper for printing;

a platen roller for the document, facing the transparent
cover;

a platen roller for the recording paper, facing the printing
elements; and

data processing means capable of creating the printing
image data containing a first to a n-th printing pixel data
respectively corresponding to the first to the n-th pixel data
in the read image data; characterized by

that the light receiving elements and the printing elements
are mounted on a same surface of the substrate;

that a feeding direction of the document in a region where
the document is faced to the transparent cover and a feeding
direction of the recording paper in a region where the recording

paper is faced to the printing elements are the same; and

that the pixel data outputted for the printing are arranged
in the order of first to n-th when the printing image data are
outputted by the printing elements onto the recording paper
5 for printing.

2. The image processing apparatus according to Claim 1,

wherein the integrated image-reading/writing head is
provided with a drive controlling circuit including a shift
10 register serially storing the pixel data contained in the
printing image data received from the data processing means
in the order of reception and in the direction of the row of
printing elements, and selectively driving the printing
elements corresponding to contents of the pixel data stored
15 in the shift register, and

wherein an inputting direction of the printing image data
to the shift register is opposite to the main scanning
direction.

20 3. The image processing apparatus according to Claim 2,

wherein the drive controlling circuit is constituted by
using a plurality of IC chips each incorporating a circuit as
a unit of the drive controlling circuit, and

wherein the IC chips being mounted on the surface of the
25 substrate mounted with the light receiving elements and the
printing elements.

4. The image processing apparatus according to Claim 2,
wherein the drive controlling circuit incorporates a
circuit as a unit of the drive controlling circuit, and
wherein the IC chips also incorporating the light receiving
5 elements.

5. The image processing apparatus according to Claim 2,
wherein the drive controlling circuit is arranged to
perform drive control of the printing elements when receiving
10 a strobe signal from the data processing means, and
wherein the light receiving elements being arranged to
perform reading of the document only while the strobe signal
being outputted from the data processing means.

15 6. The image processing apparatus according to Claim 1,
wherein the integrated image-reading/writing head is
provided with a case fitted with the transparent cover, the
case being assembled to the substrate to enclose the light
receiving elements, allowing part of the substrate to extend
20 out of the case, and
wherein the printing elements being mounted on the extended
part of the substrate.

7. The image processing apparatus according to Claim 1,
25 wherein the surface of the substrate mounted with the light
receiving elements and the printing elements is mounted with
a light source for illumination of the document.

8. The image processing apparatus according to Claim 1, wherein the printing elements are heating elements.

9. An image processing apparatus comprising:

5 an integrated image-reading/writing head including a transparent cover, a substrate opposed to and spaced from the transparent cover, a plurality of light receiving elements mounted in a row on the substrate and capable of reading in a main scanning direction an image on a document faced onto
10 the transparent cover whereby outputting line by line read image data containing a first to an n-th pixel data, and a plurality of printing elements mounted in a row generally in parallel to the light receiving elements on the substrate and capable of outputting printing image data onto a recording
15 paper for printing;

a platen roller for the document, facing the transparent cover;

a platen roller for the recording paper, facing the printing elements; and

20 data processing means capable of creating the printing image data containing a first to a n-th printing pixel data respectively corresponding to the first to the n-th pixel data in the read image data; characterized by

that the light receiving elements and the printing elements
25 are mounted on a same surface of the substrate;

that a feeding direction of the document in a region where the document is faced to the transparent cover and a feeding

direction of the recording paper in a region where the recording paper is faced to the printing elements are opposite to each other; and

that the pixel data outputted for the printing are arranged in the order of n-th to first when the printing image data are outputted by the printing elements onto the recording paper for printing.

10. The image processing apparatus according to Claim 9,

wherein the integrated image-reading/writing head is provided with a drive controlling circuit including a shift register serially storing the pixel data contained in the printing image data received from the data processing means in the order of reception and in the direction of the row of printing elements, and selectively driving the printing elements corresponding to contents of the pixel data stored in the shift register, and

wherein an inputting direction of the printing image data to the shift register is the main scanning direction.

11. The image processing apparatus according to Claim 10,

wherein the drive controlling circuit is constituted by using a plurality of IC chips each incorporating a circuit as a unit of the drive controlling circuit, and

wherein the IC chips being mounted on the surface of the substrate mounted with the light receiving elements and the printing elements.

12. The image processing apparatus according to Claim 10,
wherein the drive controlling circuit incorporates a
circuit as a unit of the drive controlling circuit, and
wherein the IC chips also incorporating the light receiving
5 elements.

13. The image processing apparatus according to Claim 10,
wherein the drive controlling circuit is arranged to
perform drive control of the printing elements when receiving
10 a strobe signal from the data processing means, and
wherein the light receiving elements being arranged to
perform reading of the document only while the strobe signal
being outputted from the data processing means.

14. The image processing apparatus according to Claim 9,
wherein the integrated image-reading/writing head is
provided with a case fitted with the transparent cover, the
case being assembled to the substrate to enclose the light
receiving elements, allowing part of the substrate to extend
20 out of the case, and

wherein the printing elements being mounted on the extended
part of the substrate.

15. The image processing apparatus according to Claim 9,
25 wherein the surface of the substrate mounted with the light
receiving elements and the printing elements is mounted with
a light source for illumination of the document.

16. The image processing apparatus according to Claim 9,
wherein the printing elements are heating elements.

ABSTRACT

The image processing apparatus (B) includes an integrated image-reading/writing head (A), platen rollers (P_1 , P_2) for a document and a recording paper, and data processing means (7) performing data processing necessary for copying an image on the document. The integrated image-reading/writing head (A), a plurality of light receiving elements (20) and a plurality of printing elements (8) are mounted on the same surface of a substrate (4). If the document (D) and the recording paper (K) are fed in the same direction, when the image on the document is copied, the pixel data outputted for the printing are arranged in the order of first to n-th. If the document (D) and the recording paper (K) are fed in opposite directions to each other, the pixel data outputted for the printing are arranged in the order of n-th to first.

FIG.1




FIG. 3




FIG.4





FIG. 5



2




FIG. 7




FIG. 9




FIG.10




FIG.11




FIG.12




FIG.13




FIG.14




FIG. 15




FIG.16




FIG.17




FIG.18




FIG.19





FIG.20



Declaration and Power of Attorney For Patent Application

特許出願宣言書

Japanese Language Declaration

私は、下欄に氏名を記載した発明者として、以下のとおり宣言する：

私の住所、郵便の宛先および国籍は、下欄に氏名に続いて記載したとおりであり、

名称の発明に関し、請求の範囲に記載した特許を求める主題の本来の、最初にして唯一の発明者である（一人の氏名のみが下欄に記載されている場合）か、もしくは本来の、最初にして共同の発明者である（複数の氏名が下欄に記載されている場合）と信じ、

その明細書を
(該当する方に印を付す)

☐ここに添付する。

☐____日に出願番号
第____号として提出し、
____日に補正した。
(該当する場合)

☐____日にPCT国際出願番号
第____号として提出し、
PCT第19条に基づき____日に補正した。
(該当する場合)

私は、前記のとおり補正した請求の範囲を含む前記明細書の内容を検討し、理解したことを陳述する。

私は、連邦規則法典第37部第1章第56条(a)項に従い、本願の審査に所要の情報を開示すべき義務を有することを認める。

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

IMAGE PROCESSING APPARATUS

the specification of which
(check one)

☐is attached hereto.

☐was filed on _____ as
Application Serial No. _____
and was amended on _____
(if applicable)

☒was described and claimed in PCT international application
No. PCT/JP99/03912 filed on
July 21, 1999
and as amended under PCT Article 19 on

(if applicable)

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above

I acknowledge the duty to disclose information which is material to the examination of this application in accordance with Title 37, Code of Federal Regulations, § 1.56(a).

Japanese Language Declaration

私は、合衆国法典第35部第119条 (a) - (d) 項または第365条 (a) - (b) 項にもとづく下記の外国特許出願または発明者証出願または少なくとも1つの合衆国以外の国を指定したPCT国際出願の外国優先権利益を主張し、さらに優先権の主張に係わる基礎出願の出願日前の出願日を有する外国特許出願または発明者証出願またはPCT国際出願を以下に明記する：

I hereby claim foreign priority benefits under Title 35, United States Code, § 119(a)-(d) or § 365(a)-(b) of any foreign application(s) for patent or inventor's certificate, or of any PCT international application which designated at least one country other than the United States, listed below and have also identified below any foreign application for patent or inventor's certificate or PCT international application having a filing date before that of the application on which priority is claimed:

Prior foreign applications

先の外国出願

(Number) (番号)	(Country) (国名)	(Day/Month/Year Filed) (出願の年月日)
Patent Application No. 10-209435	Japan	24/7/1998

(Number) (番号)	(Country) (国名)	(Day/Month/Year Filed) (出願の年月日)
------------------	-------------------	------------------------------------

(Number) (番号)	(Country) (国名)	(Day/Month/Year Filed) (出願の年月日)
------------------	-------------------	------------------------------------

(Number) (番号)	(Country) (国名)	(Day/Month/Year Filed) (出願の年月日)
------------------	-------------------	------------------------------------

(Number) (番号)	(Country) (国名)	(Day/Month/Year Filed) (出願の年月日)
------------------	-------------------	------------------------------------

Priority claimed

優先権の主張

<input checked="" type="checkbox"/>	<input type="checkbox"/>
Yes あり	No なし

<input type="checkbox"/>	<input type="checkbox"/>
Yes あり	No なし

<input type="checkbox"/>	<input type="checkbox"/>
Yes あり	No なし

<input type="checkbox"/>	<input type="checkbox"/>
Yes あり	No なし

<input type="checkbox"/>	<input type="checkbox"/>
Yes あり	No なし

私は、合衆国法典第35部第120条にもとづく下記の合衆国特許出願の利益または第365条 (c) 項にもとづく合衆国を指定するPCT国際出願の利益を主張し、本願の請求の範囲各項に記載の主題が合衆国法典第35部112条第1項に規定の態様で先の合衆国出願に開示されていない限度において、先の出願の出願日と本願の国内出願日またはPCT国際出願日の間に公表された連邦規則法典第37部第1章第56条 (a) 項に記載の所要の情報を開示すべき義務を有することを認める：

I hereby claim the benefit under Title 35, United States Code, § 120 of any United States application(s), or § 365(c) of any PCT international application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT international application in the manner provided by the first paragraph of Title 35, United States Code, § 112, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, § 1.56(a) which occurred between the filing date of the prior application and the national or PCT international filing date of this application:

(Application Serial No.) (出願番号)	(Filing Date) (出願日)	(現況) (特許済み、係属中、放棄済み)	(Status) (patented, pending, abandoned)
------------------------------------	------------------------	-------------------------	--

(Application Serial No.) (出願番号)	(Filing Date) (出願日)	(現況) (特許済み、係属中、放棄済み)	(Status) (patented, pending, abandoned)
------------------------------------	------------------------	-------------------------	--

Japanese Language Declaration

私は、ここに自己の知識にもとづいて行った陳述がすべて真実であり、自己の有する情報および信ずるところに従って行った陳述が真実であると信じ、さらに故意に虚偽の陳述等を行った場合、合衆国法典第18部第1001条により、罰金もしくは禁固に処せられるか、またはこれらの刑が併科され、またかかる故意による虚偽の陳述が本願ないし本願に対して付与される特許の有効性を損なうことがあることを認識して、以上の陳述を行ったことを宣言する。

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

委任状：私は、下記発明者として、以下の代理人をここに選任し、本願の手続を遂行すること並びにこれに関する一切の行為の特許商標庁に対して行うことを委任する。
(代理人氏名および登録番号を明記のこと)

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and /or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith. (list name and registration number)

Michael D. Bednarek, Regn. No. 32, 329

Lawrence J. Gotts, Regn. No. 31, 163

Aslan Baghdadi, Regn. No. 34, 542

Elizabeth M. Roesel, Regn. No. 34, 878

David C. Isaacson, Regn. No. 38, 500

書類の送付先：

Michael D. Bednarek

SHAW PITTMAN

1650 Tysons Boulevard

McLean, VA 22102-4859

Send Correspondence to:

Michael D. Bednarek

SHAW PITTMAN

1650 Tysons Boulevard,

McLean, VA 22102-4859

直通電話連絡先：(名称及び電話番号)

Michael D. Bednarek at 703/770-7606

Direct Telephone Calls to: (name and telephone number)

Michael D. Bednarek at 703/770-7606

Japanese Language Declaration

唯一のまたは第一の発明者の氏名	Full name of sole or first inventor
10	Hisayoshi Fujimoto
同発明者の署名	Inventor's signature
日付	Date
	Hisayoshi Fujimoto December 25, 2000
住所	Residence
	c/o ROHM CO., LTD. Kyoto, Japan JPX
国籍	Citizenship Japan
郵便の宛先	Post Office Address
	c/o ROHM CO., LTD. 21, Saiin Mizosaki-cho, Ukyo-ku, Kyoto-shi, Kyoto 615-8585 Japan

第2の共同発明者の氏名 (該当する場合)	Full name of second joint inventor, if any
20	Hiroaki Onishi
同第2発明者の署名	Second Inventor's signature
日付	Date
	Hiroaki Onishi December 25, 2000
住所	Residence
	c/o ROHM CO., LTD. Kyoto, Japan JPX
国籍	Citizenship Japan
郵便の宛先	Post Office Address
	c/o ROHM CO., LTD. 21, Saiin Mizosaki-cho, Ukyo-ku, Kyoto-shi, Kyoto 615-8585 Japan

第3の共同発明者の氏名 (該当する場合)	Full name of third joint inventor, if any
30	Toshihiko Takakura
同第3発明者の署名	Third Inventor's signature
日付	Date
	Toshihiko Takakura December 25, 2000
住所	Residence
	c/o ROHM CO., LTD. Kyoto, Japan JPX
国籍	Citizenship Japan
郵便の宛先	Post Office Address
	c/o ROHM CO., LTD. 21, Saiin Mizosaki-cho, Ukyo-ku, Kyoto-shi, Kyoto 615-8585 Japan

第4の共同発明者の氏名 (該当する場合)	Full name of fourth joint inventor, if any
40	Norihiro Imamura
同第4発明者の署名	Fourth Inventor's signature
日付	Date
	Norihiro Imamura December 25, 2000
住所	Residence
	c/o ROHM CO., LTD. Kyoto, Japan JPX
国籍	Citizenship Japan
郵便の宛先	Post Office Address
	c/o ROHM CO., LTD. 21, Saiin Mizosaki-cho, Ukyo-ku, Kyoto-shi, Kyoto 615-8585 Japan

第5の共同発明者の氏名 (該当する場合)	Full name of fifth joint inventor, if any
同第5発明者の署名	Fifth Inventor's signature
日付	Date
住所	Residence
国籍	Citizenship
郵便の宛先	Post Office Address